



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022  
S. Zeno di Cassola (VI) Italy  
Tel. +39 0424 570891  
info@raasm.com

## P/N 2011010

Air operated pump s. C20F for oil with 50 kg reservoir (external  $\varnothing$  340÷385 mm), R 50:1 and overpressure reversing valve

### AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

### FEATURES

Flow rate	1330 cm <sup>3</sup> /min
Tank capacity	50 ÷ 60 kg
Pressure ratio	50:1
Air inlet connection	G 1/4" (f)
Lubricant outlet connection	G 1/4" (f)
Working temperature	-25 ÷ +60 °C
Lubricant	oils > 40 cSt
Drum internal $\varnothing$	340 ÷ 385 mm
Pump(R 50:1)	p/n 62674
Drum cover	p/n 10/503
Membrane	-
Packing	No. 2 - 0,086 m <sup>3</sup>
Net weight	13,4 kg
Gross weight	14 kg



### OVERALL DIMENSIONS (mm)

