



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

## P/N 1561005

Motor operated pump s. C15B18 for oil 24 V DC, remote control with 2 pumping elements, 10 litres reservoir, min level indicator and solenoid valve

### AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

### FEATURES

|                             |                              |
|-----------------------------|------------------------------|
| Flow rate                   | 8,54 cm <sup>3</sup> /min    |
| Tank capacity               | 10 l                         |
| Reducer ratio               | -                            |
| Lubricant inlet connection  | by hydraulic greaser         |
| Lubricant outlet connection | G 3/8" (f)                   |
| N° of pistons               | 2                            |
| Working temperature         | -25 ÷ +60 °C                 |
| Compatible fluids           | oils > 40 cSt                |
| Supply                      | 24 V DC                      |
| Protection degree           | IP55                         |
| Velocity                    | -                            |
| Packing                     | No. 1 - 0,048 m <sup>3</sup> |
| Net weight                  | 6,4 kg                       |
| Gross weight                | 12 kg                        |



### OVERALL DIMENSIONS (mm)

