



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

P/N 1561185

Motor operated pump s. C15B18 for oil 24 V DC, remote control with 4 pumping elements, 10 litres reservoir, min level indicator and solenoid valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

| | |
|-----------------------------|------------------------------|
| Flow rate | 17,08 cm ³ /min |
| Tank capacity | 10 l |
| Reducer ratio | - |
| Lubricant inlet connection | by hydraulic greaser |
| Lubricant outlet connection | G 3/8" (f) |
| N° of pistons | 4 |
| Working temperature | -25 ÷ +60 °C |
| Compatible fluids | oils > 40 cSt |
| Supply | 24 V DC |
| Protection degree | IP55 |
| Velocity | - |
| Packing | No. 1 - 0,048 m ³ |
| Net weight | 6,4 kg |
| Gross weight | 12 kg |



OVERALL DIMENSIONS (mm)

