



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 1570575

Motor operated pump s. C15S for oil 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 6 poles and 4 pumping elements, R 35:1, 30 litres reservoir, min level indicator and solenoid valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

Flow rate	108 cm ³ /min
Tank capacity	30 l
Reducer ratio	35:1
Lubricant inlet connection	G 1/2" (f)
Lubricant outlet connection	G 3/8" (f)
N° of pistons	4
Working temperature	-25 ÷ +60 °C
Compatible fluids	oils > 40 cSt
Supply	230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz
Protection degree	-
Velocity	6 poles: 870 ÷ 1100 rpm
Packing	No. 1 - 0,235 m ³
Net weight	36,6 kg
Gross weight	49,8 kg



OVERALL DIMENSIONS (mm)

