



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 2000095

Motor operated pump s. C20P for grease 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz with 2 pumping element \varnothing 10 mm, 40 litres reservoir and min level indicator

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

Flow rate	400 cm ³ /min
Tank capacity	100 l
Lubricant inlet connection	G 1/2" (f)
Lubricant outlet connection	G 3/8" (f)
Dosing piston \varnothing	10 mm
Working temperature	-25 ÷ +60 °C
Lubricant	grease max NLGI 2
Supply	230/400 V AC - 50 Hz - 276/480 V AC - 60 Hz
Velocity	1370 ÷ 1640 rpm
Packing	No. 1 - 0,435 m ³
Net weight	75,7 kg
Gross weight	92,5 kg



OVERALL DIMENSIONS (mm)

