



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

P/N 2000425

Motor operated pump s. C20P for oil 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz with 2 pumping element \varnothing 7 mm, 100 litres reservoir and min level indicator

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

Flow rate	160 cm ³ /min
Tank capacity	40 l
Lubricant inlet connection	G 1/2" (f)
Lubricant outlet connection	G 3/8" (f)
Dosing piston \varnothing	7 mm
Working temperature	-25 ÷ +60 °C
Lubricant	oils > 40 cSt
Supply	230/400 V AC - 50 Hz - 276/480 V AC - 60 Hz
Velocity	1370 ÷ 1640 rpm
Packing	No. 1 - 0,268 m ³
Net weight	61,3 kg
Gross weight	77,7 kg



OVERALL DIMENSIONS (mm)

