



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 2070170

Motor operated pump s. C20S for grease 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 4 poles and 4 pumping element, R 70:1, 30 liters reservoir, min level indicator and overpressure reversing valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

| | |
|-----------------------------|--|
| Flow rate | 80 cm ³ /min |
| Tank capacity | 30 l |
| Reducer ratio | 70:1 |
| Lubricant inlet connection | G 1/2" (f) |
| Lubricant outlet connection | G 1/4" (f) |
| N° of pistons | 4 |
| Working temperature | -25 ÷ +60 °C |
| Compatible fluids | grease max NLGI 2 |
| Supply | 230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz |
| Protection degree | - |
| Velocity | 4 poles: 1370 ÷ 1660 rpm |
| Packing | No. 1 - 0,208 m ³ |
| Net weight | 34,7 kg |
| Gross weight | 46,9 kg |



OVERALL DIMENSIONS (mm)

