



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

P/N 2070560

Motor operated pump s. C20S for oil 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 6 poles and 2 pumping element, R 70:1, 30 liters reservoir, min level indicator and overpressure reversing valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

| | |
|-----------------------------|--|
| Flow rate | 28 cm ³ /min |
| Tank capacity | 30 l |
| Reducer ratio | 70:1 |
| Lubricant inlet connection | G 1/2" (f) |
| Lubricant outlet connection | G 1/4" (f) |
| N° of pistons | 2 |
| Working temperature | -25 ÷ +60 °C |
| Compatible fluids | oils > 40 cSt |
| Supply | 230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz |
| Protection degree | - |
| Velocity | 6 poles: 870 ÷ 1100 rpm |
| Packing | No. 1 - 0,208 m ³ |
| Net weight | 34,4 kg |
| Gross weight | 46,6 kg |



OVERALL DIMENSIONS (mm)

