



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

P/N 3070020

Motor operated pump s. C30S for grease 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 4 poles and 2 pumping elements, R 70:1, 10 litres reservoir and min level indicator

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

| | |
|-----------------------------|--|
| Flow rate | 40 cm ³ /min |
| Tank capacity | 10 l |
| Reducer ratio | 70:1 |
| Lubricant inlet connection | G 1/2" (f) |
| Lubricant outlet connection | G 3/8" (f) |
| N° of pistons | 2 |
| Working temperature | -25 ÷ +60 °C |
| Compatible fluids | grease max NLGI 2 |
| Supply | 230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz |
| Protection degree | - |
| Velocity | 4 poles: 1370 ÷ 1660 rpm |
| Packing | No. 1 - 0,144 m ³ |
| Net weight | 27,8 kg |
| Gross weight | 39,6 kg |



OVERALL DIMENSIONS (mm)

