



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

## P/N 3070170

Motor operated pump s. C30S for grease 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 4 poles and 4 pumping elements, R 70:1, 30 litres reservoir and min level indicator

### AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

### FEATURES

|                             |  |
|-----------------------------|--|
| Flow rate                   | 80 cm <sup>3</sup> /min                        |
| Tank capacity               | 30 l   |
| Reducer ratio               | 70:1   |
| Lubricant inlet connection  | G 1/2" (f)                                     |
| Lubricant outlet connection | G 3/8" (f)                                     |
| N° of pistons               | 4  |
| Working temperature         | -25 ÷ +60 °C                                   |
| Compatible fluids           | grease max NLGI 2                              |
| Supply                      | 230/400 V AC - 50 Hz -<br>275/480 V AC - 60 Hz |
| Protection degree           | -  |
| Velocity                    | 4 poles: 1370 ÷ 1660<br>rpm                    |
| Packing                     | No. 1 - 0,208 m <sup>3</sup>                   |
| Net weight                  | 33 kg  |
| Gross weight                | 45,2 kg  |



### OVERALL DIMENSIONS (mm)

