



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

P/N 3070230

Motor operated pump s. C30S for grease 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 6 poles and 4 pumping elements, R 70:1, 30 litres reservoir and min level indicator

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

Flow rate	56 cm ³ /min
Tank capacity	30 l
Reducer ratio	70:1
Lubricant inlet connection	G 1/2" (f)
Lubricant outlet connection	G 3/8" (f)
N° of pistons	4
Working temperature	-25 ÷ +60 °C
Compatible fluids	grease max NLGI 2
Supply	230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz
Protection degree	-
Velocity	6 poles: 870 ÷ 1100 rpm
Packing	No. 1 - 0,208 m ³
Net weight	33 kg
Gross weight	45,2 kg



OVERALL DIMENSIONS (mm)

